

01 Dec 2017

Shockwave Interaction with a Cylindrical Structure

Phillip R. Mulligan

Missouri University of Science and Technology, pmulligan@mst.edu

Follow this and additional works at: https://scholarsmine.mst.edu/geosci_geo_peteng_facwork



Part of the [Explosives Engineering Commons](#)

Recommended Citation

P. R. Mulligan, "Shockwave Interaction with a Cylindrical Structure," *Bulletin of the American Physical Society*, vol. 62, no. 9, AIP Publishing, Dec 2017.

This Article - Conference proceedings is brought to you for free and open access by Scholars' Mine. It has been accepted for inclusion in Geosciences and Geological and Petroleum Engineering Faculty Research & Creative Works by an authorized administrator of Scholars' Mine. This work is protected by U. S. Copyright Law. Unauthorized use including reproduction for redistribution requires the permission of the copyright holder. For more information, please contact scholarsmine@mst.edu.

Abstract Submitted
for the SHOCK17 Meeting of
The American Physical Society

Shockwave Interaction with a Cylindrical Structure PHILLIP

MULLIGAN, Dagaz Technologies — An increased understanding of the shockwave interaction with a cylindrical structure is the foundation for developing a method to explosively seal a pipe similar to the Deepwater Horizon accident in the Gulf of Mexico. Shockwave interactions with a cylindrical structure have been a re-occurring focus of energetics research. Some of the most notable contributions of non-destructive tests are described in “The Effects of Nuclear Weapons” (Glasstone, 1962). The work presented by Glasstone examines shockwave interaction from a 20-megaton bomb with a cylindrical structure. However, the data is limited to a peak overpressure of less than 25 psi, requiring several miles between the structure and the charge. The research presented in the following paper expands on the work Glasstone described by examining the shockwaves from 90, 180, and 270-gram C-4 charges interacting with a 6-inch diameter cylindrical structure positioned 52-inches from the center of the charge. The three charge weights that were tested in this research generated a peak overpressures of approximately 15, 25, and 40 psi, respectively. This research examines the peak pressure and total impulse from each charge acting on the cylindrical structure as well as the formation of vortices on the “backside” of the cylinder surface. This paper describes the methodology and findings of this study as well as examines the causality and implications of its results on our understanding of the shockwave interaction with a cylindrical structure.

Phillip Mulligan
Dagaz Technologies

Date submitted: 24 Feb 2017

Electronic form version 1.4