

7-1-2012

# The Effects of the Flyer Plate's Radius of Curvature on the Performance of an Explosively Formed Projectile

Phillip R. Mulligan

*Missouri University of Science and Technology*, pmulligan@mst.edu

Jason Baird

*Missouri University of Science and Technology*, jbaird@mst.edu

Joshua Hoffman

Follow this and additional works at: [https://scholarsmine.mst.edu/geosci\\_geo\\_peteng\\_facwork](https://scholarsmine.mst.edu/geosci_geo_peteng_facwork)



Part of the [Explosives Engineering Commons](#)

---

## Recommended Citation

P. R. Mulligan et al., "The Effects of the Flyer Plate's Radius of Curvature on the Performance of an Explosively Formed Projectile," *AIP Conference Proceedings*, vol. 1426, pp. 1023-1026, AIP Publishing, Jul 2012.

The definitive version is available at <https://doi.org/10.1063/1.3686452>

This Article - Conference proceedings is brought to you for free and open access by Scholars' Mine. It has been accepted for inclusion in Geosciences and Geological and Petroleum Engineering Faculty Research & Creative Works by an authorized administrator of Scholars' Mine. This work is protected by U. S. Copyright Law. Unauthorized use including reproduction for redistribution requires the permission of the copyright holder. For more information, please contact [scholarsmine@mst.edu](mailto:scholarsmine@mst.edu).

Abstract Submitted  
for the SHOCK11 Meeting of  
The American Physical Society

**The Effects of the Flyer Plate's Radius of Curvature on the Performance of an Explosively Formed Projectile** PHILLIP MULLIGAN, JASON BAIRD, JOSHUA HOFFMAN — An explosively formed projectile (EFP) is known for its ability to penetrate vehicle armor effectively. Understanding how an EFP's physical parameters affect its performance is crucial to development of an armor capable of defeating such devices. The present study uses two flyer plate radii of curvature to identify the experimental effects the flyer plate's radius of curvature has on the measured projectile velocity, depth of penetration, and projectile shape of an EFP. The Gurney equation is an algebraic relationship for estimating the velocity imparted to a metal plate in contact with detonating explosives (1). In their attempts to calculate an EFP theoretical flyer plate velocity, the authors of this research used the open-faced-sandwich Gurney equation, whereby a semi-infinite slab of explosive is in intimate contact with a semi-infinite metal flyer plate. This equation uses the flyer-weight to charge-weight ratio and the specific explosive kinetic energy to calculate the theoretical flyer plate velocity. Two EFP designs that have two different flyer plate radii of curvature, but the same physical parameters and the same flyer-weight to charge-weight ratio should theoretically have the same velocity. Test results indicate the flyer plate's radius of curvature does not affect the projectile's velocity and that using a flat flyer plate negatively affects projectile penetration and formation.

Phillip Mulligan

Date submitted: 17 Feb 2011

Electronic form version 1.4