

Missouri University of Science and Technology Scholars' Mine

Electrical and Computer Engineering Faculty Research & Creative Works

Electrical and Computer Engineering

04 May 2018

NMR Studies of Loaded Microspheres

Ming Huang

Sisi Chen

Rex E. Gerald II

Jie Huang Missouri University of Science and Technology, jieh@mst.edu

et. al. For a complete list of authors, see https://scholarsmine.mst.edu/ele_comeng_facwork/4035

Follow this and additional works at: https://scholarsmine.mst.edu/ele_comeng_facwork

Part of the Chemistry Commons, and the Electrical and Computer Engineering Commons

Recommended Citation

M. Huang et al., "NMR Studies of Loaded Microspheres," *Proceedings of the 59th Experimental Nuclear Magnetic Resonance Conference (2019, Orlando, FL)*, SPIE, May 2018.

This Article - Conference proceedings is brought to you for free and open access by Scholars' Mine. It has been accepted for inclusion in Electrical and Computer Engineering Faculty Research & Creative Works by an authorized administrator of Scholars' Mine. This work is protected by U. S. Copyright Law. Unauthorized use including reproduction for redistribution requires the permission of the copyright holder. For more information, please contact scholarsmine@mst.edu.

NMR Studies of Loaded Microspheres

Ming Huang¹, Sisi Chen², Rex E. Gerald II³, Jie Huang⁴, Klaus Woelk¹

¹ Department of Chemistry, Missouri S&T, 400 W 11th St., Rolla, MO 65409-0010, USA

² Brewer Science, 2401 Brewer Dr., Rolla, MO 65401, USA

³ American Inventor Institute, 141 Willows Edge Ct, Unit B, Willow Springs, IL 60480, USA

⁴ Department of Electrical and Computer Engineering, Missouri S&T, 301 W 16th St., Rolla, MO 65409-0040, USA

Porous-wall hollow glass microspheres (PWHGMs) are a novel form of glass materials that consist of 1-µm-thick porous silica shells, 20-100 µm in diameter, with a hollow cavity in the center. Utilizing the central cavity for material storage and the porous walls for controlled release is a unique combination that renders PWHGMs a superior vehicle for targeted drug delivery. In this study, NMR spectroscopy was used to characterize PWHGMs for the first time. A vacuum-based loading system was developed to load PWHGMs with various compounds followed by a washing procedure that uses solvents immiscible with the target material. Immiscible binary model systems (chloroform/water, n-dodecane/water), as well as the hydrolysis of isopropyl acetate, were investigated to obtain NMR evidence for material loading into PWHGMs and their subsequent release to the surrounding solutions. The NMR peaks of the loaded materials were distinguishable from the NMR peaks of the materials in the surrounding solution. The formation of the reaction product isopropanol provided evidence of encounters of isopropyl acetate in the microspheres and concentrated H₂SO₄ added to the surrounding solution. Also, microspheres loaded with H₂O were suspended in D₂O and monitored to obtain quantitative release kinetics of H₂O encapsulated in PWHGMs with time constants of 18 - 20 minutes and 160 minutes. The results demonstrate that NMR is a particularly useful tool to study developments and applications of PWHGMs in targeted drug delivery.




Figure 1. SEM images of microsphere shell and ¹H NMR spectrum of CHCl₃ inside of the microspheres suspended in D₂O. (a) a hole on the microsphere surface; (b) the enlarged hole; (c) interception of the microsphere shell; (d) channels through the microsphere shell; (e) peaks from left to right are assigned to dissolved CHCl₃ in D₂O (7.55 ppm), CHCl₃ inside microspheres (7.20 ppm), and HOD (4.63 ppm); (f) expansion of NMR spectrum from 8 ppm to 6.5 ppm showing a comparison of the dissolved CHCl₃ peak with the microspheres peak